

ACRILID PROTECT COATING

Coloured finishing for indoor and outdoor, resistant to salty air

Liquid coloured coating for indoor and outdoor, water-repellent, breathable, latex based, used as protective finishing for external façades and internal walls. The product is studied to finish external thermal and acoustic plaster realized with *Diathonite*, as it impedes the water absorption by the masonry. The finishing is able to avoid the carbonation of concrete caused by weathering agents. Ideal product for salty air.

BENEFITS

- Highly elastic.
- Breathable.
- Water-repellent.
- High resistance to weathering agents, UV rays and salty air.
- Resistant to both high and low temperatures.
- Fibre-reinforced
- Easy and quick application
- Solvent free

APPLICATION FIELDS

The product is designed for the decoration of walls exposed to salty air: façades, old and new plasters, thermal plaster such as *Diathonite Evolution* (see technical data sheet) or external thermal systems. *Acrilid protect coating* creates a smooth finish and can be used in different situations: concrete or plasters. Product suitable for indoor and outdoor environments.

YIELD

0.50 kg/m² to obtain a smooth finishing;
0.70 kg/m² to obtain a rough finishing.

COLOUR

See the list of the customized NCS products at the end of this technical data sheet.

PACKAGING

25 kg plastic bucket.
Pallet: 48 buckets (1200 kg).

STORAGE

Store the product in its original containers perfectly closed, in well ventilated areas, away from sunlight, water and ice, at temperatures between +5°C (41°F) and +35°C (95°F).
Storage time: 24 months.

PREPARATION OF SUPPORT

The substrate must be completely hardened and resistant enough. The surface must be carefully clean, well consolidated, without debris or detaching parts and perfectly levelled.

Before the product application, it is recommended to cover threshold, window fixtures and each element that will not be coated. Eventual lesions or damaged parts of the support must be restored before the product application.

It is recommended to apply the paint within 30 days from the end of the smoothing and anyway before the winter season.



Diasen srl

Zona Industriale Berbentina, 5 Sassoferrato ANCONA
14

UNI EN 1504-2

Products and systems for the protection and the
restoration of concrete structures –
Part 2: Protection system of the concrete surface

Water vapour permeability:

$\mu = 88$



For application videos,
product page, safety data
sheet and other information.

Finish - liquid

Whereas all indications and recommendations supplied herein are stated to the best of our experience and knowledge, they should be considered as indicative only and should be confirmed by exhaustive practical applications. Diasen doesn't know the peculiarity of the processing, or the characteristics of the support. Therefore the applicator should carry out preliminary tests, to verify the suitability to the foreseen application, and in any case he will take the responsibility of the intended use. In case of uncertainties or doubts, please contact the company's technical department, provided that this is only a simple assistance for the applicator: he should have the appropriate capabilities and experience to determine the more suitable solution. Always respect the latest update of the technical sheet available on www.diasen.com.

ACRILID PROTECT COATING

Coloured finishing for indoor and outdoor, resistant to salty air

Technical data		
Feature		Unit
Yield	0.50 kg/m ² for a smooth finish 0.70 kg/m ² for a rough finish	kg/m ²
Aspect	liquid	-
Colour	See the list of customized NCS colours	-
Dilution	If necessary, max 8% of water	-
Waiting time between 1 st and 2 nd coat (T=20°C/ 68°F; R. H. 40%)	4	hours
Application temperature	+5 /+35 41/95	°C °F
Maximum humidity	70%	-
Drying time (T=20°C; U.R. 40%)	5	hours
Storage	24 months in original containers and dry places	months
Packaging	25 kg plastic bucket	kg

Final performances		Unit	Regulation	Result
Sea salt resistance	-	-	-	excellent
Weathering Test	2000 hours (> 10 years*)	hours / years	UNI EN ISO 11507	-
Water vapour permeability	$\mu = 88$ $S_D = 0.05$	- m	UNI EN ISO 7783	class I – high breathability
Solid content	65%	-	-	-
Superficial drying temperature	+5 +41	°C °F	-	-

* 1680 hours of weathering test correspond to about 10 years. This correspondence is merely indicative and it may change according to the climatic conditions of the place where the product will be used.

The above data, even if carried out according to regulated tests, are indicative and they may change when specific building site condition vary.

Finish - liquid

Whereas all indications and recommendations supplied herein are stated to the best of our experience and knowledge, they should be considered as indicative only and should be confirmed by exhaustive practical applications. Diasen doesn't know the peculiarity of the processing, or the characteristics of the support. Therefore the applicator should carry out preliminary tests, to verify the suitability to the foreseen application, and in any case he will take the responsibility of the intended use. In case of uncertainties or doubts, please contact the company's technical department, provided that this is only a simple assistance for the applicator: he should have the appropriate capabilities and experience to determine the more suitable solution. Always respect the latest update of the technical sheet available on www.diasen.com.

ACRILID PROTECT COATING

Coloured finishing for indoor and outdoor, resistant to salty air

Diathonite plasters or new plasters

Make sure that the surface of the plaster is less rough as possible and apply the smoother *Argacem HP* or *Argacem MP* (see technical data sheets). Before the application, apply the specific fixative *D20* (see technical data sheet).

Old plasters

Make sure that the plaster is compact and well bonded to the support, otherwise totally or partially remove it and re-make it.

In case of painted plasters, remove the detaching paints, fill eventual imperfections and then smooth the surface with sandpaper.

Before applying *Acrilid Protect Coating*, treat the surface with the fixative *D18* or *D20* (see technical data sheet).

Concrete

In case of damaged or crumbly concrete, restore it with the mortar *Rebuild CLS* (see technical data sheet).

For the treatment of iron bars apply *Anticorrosive 2K* (see technical data sheet).

Concrete supports must be sufficiently cured.

In case of smooth concrete, on not moist support, use the primer *Grip Primer* (see technical data sheet).

Smooth concrete

On smooth and non absorbent surfaces use the specific primer *Grip Primer* (see technical data sheet).

For supports not mentioned in this technical data sheet, please contact Diasen technical office.

MIXING

Perfectly mix the product before the use to make it homogeneous. In extremely hot climatic conditions it is possible to add at maximum 8% of clean water.

Never add other substances to the mixture.

APPLICATION

1. Wait for the complete drying of the primer or of the fixative used.
2. Apply a first layer of *Acrilid Protect Coating* by short haired roll or by airless and wait for the complete drying (about 4 hours at 20°C/68°F and 40% relative humidity). In case of rain over not perfectly dry product carefully verify the suitability of the next covering.
3. Apply a second layer of *Acrilid Protect Coating* to completely cover the substrate. For a better result, it is recommended to cross the coats.

DRYING TIME

At a temperature of 20°C/68°F and 40% relative humidity, the product dries in about 5 hours.

- Drying time is influenced by environmental relative humidity and by temperature and it may significantly change.

If applied with a higher yield than the expected one, drying time can significantly increase.

SUGGESTIONS

- Do not apply at environmental temperature or at support temperature lower than +5°C (41°F) and higher than +30°C (86°F).
- During summer season, apply the product in the cooler hours of the day.
- Do not apply with imminent threat of rain or ice, in conditions of strong fog or with relative humidity higher than 70%.
- Apply the product over completely dry surfaces.
- Store the unused product in its original package.

CLEANING

Wash tools with water as soon after use.

SAFETY

While handling, always use personal protective equipment and respect the instructions described in product safety data sheet.

Finish - liquid

Whereas all indications and recommendations supplied herein are stated to the best of our experience and knowledge, they should be considered as indicative only and should be confirmed by exhaustive practical applications. Diasen doesn't know the peculiarity of the processing, or the characteristics of the support. Therefore the applicator should carry out preliminary tests, to verify the suitability to the foreseen application, and in any case he will take the responsibility of the intended use. In case of uncertainties or doubts, please contact the company's technical department, provided that this is only a simple assistance for the applicator: he should have the appropriate capabilities and experience to determine the more suitable solution. Always respect the latest update of the technical sheet available on www.diasen.com.

ACRILID PROTECT COATING

Coloured finishing for indoor and outdoor, resistant to salty air

CUSTOMIZED NCS COLOUR

NCS code are listed in alphabetical order for an easier research.

S 0300-N	S 0505-Y80R	S 0510-Y50R	S 0520-Y60R	S 0804-R90B
S 0500-N	S 0505-Y90R	S 0510-Y60R	S 0520-Y70R	S 0804-Y10R
S 0502-B	S 0507-B	S 0510-Y70R	S 0520-Y80R	S 0804-Y30R
S 0502-B50G	S 0507-B20G	S 0510-Y80R	S 0520-Y90R	S 0804-Y50R
S 0502-G	S 0507-B80G	S 0510-Y90R	S 0530-G50Y	S 0804-Y70R
S 0502-G50Y	S 0507-G	S 0515-G20Y	S 0530-G60Y	S 0804-Y90R
S 0502-R	S 0507-G40Y	S 0515-G40Y	S 0530-G70Y	S 0907-B20G
S 0502-R50B	S 0507-G80Y	S 0515-G60Y	S 0530-G80Y	S 0907-B80G
S 0502-Y	S 0507-R	S 0515-G80Y	S 0530-G90Y	S 0907-G20Y
S 0502-Y50R	S 0507-R20B	S 0515-G90Y	S 0530-R	S 0907-G60Y
S 0505-B	S 0507-R40B	S 0515-R	S 0530-Y	S 0907-G90Y
S 0505-B20G	S 0507-R80B	S 0515-R10B	S 0530-Y10R	S 0907-R10B
S 0505-B50G	S 0507-Y	S 0515-R20B	S 0530-Y20R	S 0907-R10B
S 0505-B80G	S 0507-Y20R	S 0515-R80B	S 0530-Y30R	S 0907-R30B
S 0505-G	S 0507-Y40R	S 0515-R90B	S 0530-Y40R	S 0907-R50B
S 0505-G10Y	S 0507-Y60R	S 0515-Y	S 0530-Y50R	S 0907-R70B
S 0505-G20Y	S 0507-Y80R	S 0515-Y10R	S 0530-Y60R	S 0907-R90B
S 0505-G30Y	S 0510-B	S 0515-Y20R	S 0530-Y70R	S 0907-Y10R
S 0505-G40Y	S 0510-B10G	S 0515-Y30R	S 0530-Y80R	S 0907-Y10R
S 0505-G50Y	S 0510-G	S 0515-Y40R	S 0530-Y90R	S 0907-Y30R
S 0505-G60Y	S 0510-G10Y	S 0515-Y50R	S 0540-G50Y	S 0907-Y50R
S 0505-G70Y	S 0510-G20Y	S 0515-Y60R	S 0540-R	S 0907-Y70R
S 0505-G80Y	S 0510-G30Y	S 0515-Y70R	S 0540-Y90R	S 0907-Y90R
S 0505-G90Y	S 0510-G40Y	S 0515-Y80R	S 0550-Y90R	S 1000-N
S 0505-R	S 0510-G50Y	S 0515-Y90R	S 0603-G40Y	S 1000-N
S 0505-R10B	S 0510-G60Y	S 0520-G30Y	S 0603-G80Y	S 1002-B
S 0505-R20B	S 0510-G70Y	S 0520-G40Y	S 0603-R20B	S 1002-B
S 0505-R30B	S 0510-G80Y	S 0520-G50Y	S 0603-R40B	S 1002-B50G
S 0505-R40B	S 0510-G90Y	S 0520-G60Y	S 0603-R60B	S 1002-B50G
S 0505-R50B	S 0510-R	S 0520-G70Y	S 0603-R80B	S 1002-G
S 0505-R60B	S 0510-R10B	S 0520-G80Y	S 0603-Y20R	S 1002-G
S 0505-R70B	S 0510-R20B	S 0520-G90Y	S 0603-Y40R	S 1002-G50Y
S 0505-R80B	S 0510-R30B	S 0520-R	S 0603-Y60R	S 1002-G50Y
S 0505-R90B	S 0510-R60B	S 0520-R10B	S 0603-Y80R	S 1002-R
S 0505-Y	S 0510-R70B	S 0520-R20B	S 0804-B50G	S 1002-R
S 0505-Y10R	S 0510-R80B	S 0520-R80B	S 0804-G20Y	S 1002-R50B
S 0505-Y20R	S 0510-R90B	S 0520-Y	S 0804-G60Y	S 1002-R50B
S 0505-Y30R	S 0510-Y	S 0520-Y10R	S 0804-G90Y	S 1002-Y
S 0505-Y40R	S 0510-Y10R	S 0520-Y20R	S 0804-R10B	S 1002-Y
S 0505-Y50R	S 0510-Y20R	S 0520-Y30R	S 0804-R30B	S 1002-Y50R
S 0505-Y60R	S 0510-Y30R	S 0520-Y40R	S 0804-R50B	S 1002-Y50R
S 0505-Y70R	S 0510-Y40R	S 0520-Y50R	S 0804-R70B	S 1005-B

Finish - liquid

Whereas all indications and recommendations supplied herein are stated to the best of our experience and knowledge, they should be considered as indicative only and should be confirmed by exhaustive practical applications. Diasen doesn't know the peculiarity of the processing, or the characteristics of the support. Therefore the applicator should carry out preliminary tests, to verify the suitability to the foreseen application, and in any case he will take the responsibility of the intended use. In case of uncertainties or doubts, please contact the company's technical department, provided that this is only a simple assistance for the applicator: he should have the appropriate capabilities and experience to determine the more suitable solution. Always respect the latest update of the technical sheet available on www.diasen.com.

ACRILID PROTECT COATING

Coloured finishing for indoor and outdoor, resistant to salty air

CUSTOMIZED NCS COLOUR

S 1005-B20G	S 1010-G70Y	S 1020-G40Y	S 1040-G70Y	S 1510-R
S 1005-B50G	S 1010-G80Y	S 1020-G50Y	S 1040-G80Y	S 1510-R10B
S 1005-B80G	S 1010-G90Y	S 1020-G60Y	S 1040-G90Y	S 1510-R20B
S 1005-G	S 1010-R	S 1020-G70Y	S 1040-Y30R	S 1510-R40B
S 1005-G10Y	S 1010-R10B	S 1020-G80Y	S 1040-Y40R	S 1510-R60B
S 1005-G20Y	S 1010-R20B	S 1020-G90Y	S 1040-Y50R	S 1510-R80B
S 1005-G30Y	S 1010-R30B	S 1020-R	S 1040-Y60R	S 1510-R90B
S 1005-G40Y	S 1010-R40B	S 1020-R10B	S 1040-Y70R	S 1510-Y
S 1005-G50Y	S 1010-R50B	S 1020-R80B	S 1040-Y80R	S 1510-Y10R
S 1005-G60Y	S 1010-R60B	S 1020-R90B	S 1040-Y90R	S 1510-Y20R
S 1005-G70Y	S 1010-R80B	S 1020-Y	S 1050-G50Y	S 1510-Y30R
S 1005-G80Y	S 1010-R90B	S 1020-Y10R	S 1050-Y30R	S 1510-Y40R
S 1005-G90Y	S 1010-Y	S 1020-Y20R	S 1050-Y40R	S 1510-Y50R
S 1005-R	S 1010-Y10R	S 1020-Y30R	S 1500-N	S 1510-Y60R
S 1005-R10B	S 1010-Y20R	S 1020-Y40R	S 1502-B	S 1510-Y70R
S 1005-R20B	S 1010-Y30R	S 1020-Y50R	S 1502-B50G	S 1510-Y80R
S 1005-R30B	S 1010-Y40R	S 1020-Y60R	S 1502-G	S 1510-Y90R
S 1005-R40B	S 1010-Y50R	S 1020-Y60R	S 1502-G50Y	S 1515-B
S 1005-R50B	S 1010-Y60R	S 1020-Y70R	S 1502-R	S 1515-B20G
S 1005-R60B	S 1010-Y70R	S 1020-Y80R	S 1502-R50B	S 1515-G20Y
S 1005-R70B	S 1010-Y80R	S 1020-Y90R	S 1502-Y	S 1515-G40Y
S 1005-R80B	S 1010-Y90R	S 1030-G40Y	S 1502-Y50R	S 1515-G60Y
S 1005-R90B	S 1015-B	S 1030-G50Y	S 1505-G80Y	S 1515-G80Y
S 1005-Y	S 1015-G20Y	S 1030-G60Y	S 1505-G90Y	S 1515-R
S 1005-Y10R	S 1015-G40Y	S 1030-G60Y	S 1505-Y	S 1515-R40B
S 1005-Y20R	S 1015-G60Y	S 1030-G70Y	S 1505-Y10R	S 1515-R60B
S 1005-Y30R	S 1015-G80Y	S 1030-G70Y	S 1505-Y20R	S 1515-R80B
S 1005-Y40R	S 1015-G90Y	S 1030-G80Y	S 1505-Y30R	S 1515-R90B
S 1005-Y50R	S 1015-R	S 1030-G90Y	S 1505-Y40R	S 1515-Y
S 1005-Y60R	S 1015-R10B	S 1030-R	S 1505-Y50R	S 1515-Y10R
S 1005-Y70R	S 1015-R20B	S 1030-R90B	S 1505-Y60R	S 1515-Y20R
S 1005-Y80R	S 1015-R60B	S 1030-Y	S 1505-Y70R	S 1515-Y30R
S 1005-Y90R	S 1015-R90B	S 1030-Y10R	S 1505-Y80R	S 1515-Y40R
S 1010-B	S 1015-Y	S 1030-Y20R	S 1505-Y90R	S 1515-Y50R
S 1010-B10G	S 1015-Y10R	S 1030-Y30R	S 1510-B	S 1515-Y60R
S 1010-B70G	S 1015-Y20R	S 1030-Y40R	S 1510-B20G	S 1515-Y70R
S 1010-B90G	S 1015-Y30R	S 1030-Y50R	S 1510-B50G	S 1515-Y80R
S 1010-G	S 1015-Y40R	S 1030-Y60R	S 1510-B80G	S 1515-Y90R
S 1010-G10Y	S 1015-Y50R	S 1030-Y70R	S 1510-G	S 2000-N
S 1010-G20Y	S 1015-Y60R	S 1030-Y80R	S 1510-G20Y	S 2002-B
S 1010-G30Y	S 1015-Y70R	S 1030-Y90R	S 1510-G40Y	S 2002-B50G
S 1010-G40Y	S 1015-Y80R	S 1040-G40Y	S 1510-G60Y	S 2002-G
S 1010-G50Y	S 1015-Y90R	S 1040-G50Y	S 1510-G80Y	S 2002-G50Y
S 1010-G60Y	S 1020-G30Y	S 1040-G60Y	S 1510-G90Y	S 2002-R

Finish - liquid

Whereas all indications and recommendations supplied herein are stated to the best of our experience and knowledge, they should be considered as indicative only and should be confirmed by exhaustive practical applications. Diasen doesn't know the peculiarity of the processing, or the characteristics of the support. Therefore the applicator should carry out preliminary tests, to verify the suitability to the foreseen application, and in any case he will take the responsibility of the intended use. In case of uncertainties or doubts, please contact the company's technical department, provided that this is only a simple assistance for the applicator: he should have the appropriate capabilities and experience to determine the more suitable solution. Always respect the latest update of the technical sheet available on www.diasen.com.

ACRILID PROTECT COATING

Coloured finishing for indoor and outdoor, resistant to salty air

CUSTOMIZED NCS COLOUR

S 2002-R50B	S 2010-G30Y	S 2020-Y60R	S 2060-G50Y	S 3010-Y10R
S 2002-Y	S 2010-G40Y	S 2020-Y70R	S 2060-Y10R	S 3010-Y20R
S 2002-Y50R	S 2010-G50Y	S 2020-Y80R	S 2060-Y20R	S 3010-Y30R
S 2005-B	S 2010-G60Y	S 2020-Y90R	S 2060-Y30R	S 3010-Y40R
S 2005-B20G	S 2010-G70Y	S 2030-B	S 2060-Y50R	S 3010-Y50R
S 2005-B80G	S 2010-G80Y	S 2030-G30Y	S 2060-Y80R	S 3010-Y60R
S 2005-G	S 2010-G90Y	S 2030-G50Y	S 2500-N	S 3010-Y70R
S 2005-G10Y	S 2010-R	S 2030-G60Y	S 2502-B	S 3010-Y80R
S 2005-G20Y	S 2010-R10B	S 2030-G70Y	S 2502-G	S 3010-Y90R
S 2005-G30Y	S 2010-R20B	S 2030-G80Y	S 2502-R	S 3020-B
S 2005-G40Y	S 2010-R30B	S 2030-G90Y	S 2502-Y	S 3020-G20Y
S 2005-G50Y	S 2010-R40B	S 2030-R	S 3000-N	S 3020-G30Y
S 2005-G60Y	S 2010-R50B	S 2030-Y	S 3005-B20G	S 3020-G40Y
S 2005-G70Y	S 2010-R60B	S 2030-Y10R	S 3005-B80G	S 3020-G50Y
S 2005-G80Y	S 2010-R70B	S 2030-Y20R	S 3005-G20Y	S 3020-G60Y
S 2005-G90Y	S 2010-R90B	S 2030-Y30R	S 3005-G50Y	S 3020-G70Y
S 2005-R	S 2010-Y	S 2030-Y40R	S 3005-G80Y	S 3020-G80Y
S 2005-R10B	S 2010-Y10R	S 2030-Y50R	S 3005-R20B	S 3020-G90Y
S 2005-R20B	S 2010-Y20R	S 2030-Y60R	S 3005-R50B	S 3020-R
S 2005-R30B	S 2010-Y30R	S 2030-Y70R	S 3005-R80B	S 3020-R10B
S 2005-R40B	S 2010-Y40R	S 2030-Y80R	S 3005-Y20R	S 3020-R20B
S 2005-R50B	S 2010-Y50R	S 2030-Y90R	S 3005-Y50R	S 3020-R40B
S 2005-R60B	S 2010-Y60R	S 2040-G60Y	S 3005-Y80R	S 3020-R50B
S 2005-R70B	S 2010-Y70R	S 2040-G70Y	S 3010-B	S 3020-R90B
S 2005-R80B	S 2010-Y80R	S 2040-Y10R	S 3010-B10G	S 3020-Y
S 2005-R90B	S 2010-Y90R	S 2040-Y20R	S 3010-B30G	S 3020-Y10R
S 2005-Y	S 2020-B10G	S 2040-Y30R	S 3010-B50G	S 3020-Y20R
S 2005-Y10R	S 2020-G30Y	S 2040-Y40R	S 3010-G	S 3020-Y30R
S 2005-Y20R	S 2020-G40Y	S 2040-Y50R	S 3010-G10Y	S 3020-Y40R
S 2005-Y30R	S 2020-G50Y	S 2040-Y60R	S 3010-G20Y	S 3020-Y50R
S 2005-Y40R	S 2020-G60Y	S 2040-Y70R	S 3010-G30Y	S 3020-Y60R
S 2005-Y50R	S 2020-G70Y	S 2040-Y90R	S 3010-G40Y	S 3020-Y70R
S 2005-Y60R	S 2020-G80Y	S 2050-G40Y	S 3010-G50Y	S 3020-Y80R
S 2005-Y70R	S 2020-G90Y	S 2050-G70Y	S 3010-G60Y	S 3020-Y90R
S 2005-Y80R	S 2020-R	S 2050-G80Y	S 3010-G70Y	S 3030-G40Y
S 2005-Y90R	S 2020-R10B	S 2050-G90Y	S 3010-G80Y	S 3030-G50Y
S 2010-B	S 2020-R70B	S 2050-Y10R	S 3010-G90Y	S 3030-G60Y
S 2010-B10G	S 2020-R80B	S 2050-Y20R	S 3010-R	S 3030-G70Y
S 2010-B30G	S 2020-Y	S 2050-Y30R	S 3010-R10B	S 3030-G90Y
S 2010-B50G	S 2020-Y10R	S 2050-Y40R	S 3010-R20B	S 3030-Y
S 2010-B70G	S 2020-Y20R	S 2050-Y50R	S 3010-R30B	S 3030-Y10R
S 2010-G	S 2020-Y30R	S 2050-Y60R	S 3010-R40B	S 3030-Y20R
S 2010-G10Y	S 2020-Y40R	S 2050-Y90R	S 3010-R50B	S 3030-Y30R
S 2010-G20Y	S 2020-Y50R	S 2060-G40Y	S 3010-Y	S 3030-Y40R

Finish - liquid

Whereas all indications and recommendations supplied herein are stated to the best of our experience and knowledge, they should be considered as indicative only and should be confirmed by exhaustive practical applications. Diasen doesn't know the peculiarity of the processing, or the characteristics of the support. Therefore the applicator should carry out preliminary tests, to verify the suitability to the foreseen application, and in any case he will take the responsibility of the intended use. In case of uncertainties or doubts, please contact the company's technical department, provided that this is only a simple assistance for the applicator: he should have the appropriate capabilities and experience to determine the more suitable solution. Always respect the latest update of the technical sheet available on www.diasen.com.

ACRILID PROTECT COATING

Coloured finishing for indoor and outdoor, resistant to salty air

CUSTOMIZED NCS COLOUR

S 3030-Y50R	S 4005-R50B	S 4030-Y80R	S 5020-R40B	S 6020-G30Y
S 3030-Y60R	S 4005-R80B	S 4030-Y90R	S 5020-Y	S 6020-G50Y
S 3030-Y70R	S 4005-Y20R	S 4040-G30Y	S 5020-Y10R	S 6020-G90Y
S 3030-Y80R	S 4005-Y50R	S 4040-G40Y	S 5020-Y20R	S 6020-Y
S 3030-Y90R	S 4005-Y80R	S 4040-G50Y	S 5020-Y40R	S 6020-Y10R
S 3040-G40Y	S 4010-B50G	S 4040-G60Y	S 5020-Y50R	S 6020-Y20R
S 3040-G50Y	S 4010-B70G	S 4040-G70Y	S 5020-Y60R	S 6020-Y30R
S 3040-G60Y	S 4010-G30Y	S 4040-G90Y	S 5020-Y70R	S 6020-Y40R
S 3040-G70Y	S 4010-G50Y	S 4040-Y	S 5020-Y80R	S 6020-Y50R
S 3040-G90Y	S 4010-G70Y	S 4040-Y10R	S 5020-Y90R	S 6020-Y60R
S 3040-Y10R	S 4010-G90Y	S 4040-Y20R	S 5030-G50Y	S 6020-Y70R
S 3040-Y30R	S 4010-R10B	S 4040-Y30R	S 5030-G70Y	S 6020-Y80R
S 3040-Y40R	S 4010-Y10R	S 4040-Y40R	S 5030-G90Y	S 6030-Y50R
S 3040-Y50R	S 4010-Y30R	S 4040-Y70R	S 5030-Y	S 6030-Y70R
S 3040-Y60R	S 4010-Y50R	S 4040-Y80R	S 5030-Y10R	S 6500-N
S 3040-Y70R	S 4010-Y70R	S 4050-Y40R	S 5030-Y20R	S 6502-R
S 3040-Y80R	S 4010-Y90R	S 4050-Y50R	S 5030-Y30R	S 6502-Y
S 3040-Y90R	S 4020-B90G	S 4050-Y60R	S 5030-Y40R	S 7000-N
S 3050-G40Y	S 4020-G30Y	S 4050-Y70R	S 5030-Y50R	S 7005-G50Y
S 3050-G50Y	S 4020-G50Y	S 4500-N	S 5030-Y60R	S 7005-G80Y
S 3050-G60Y	S 4020-G70Y	S 4502-B	S 5030-Y70R	S 7005-R20B
S 3050-G70Y	S 4020-G90Y	S 4502-R	S 5030-Y80R	S 7005-R50B
S 3050-G80Y	S 4020-R40B	S 4502-Y	S 5040-Y40R	S 7005-Y20R
S 3050-Y	S 4020-R50B	S 4550-Y80R	S 5040-Y60R	S 7005-Y50R
S 3050-Y10R	S 4020-R60B	S 5000-N	S 5040-Y70R	S 7005-Y80R
S 3050-Y20R	S 4020-Y	S 5005-B20G	S 5500-N	S 7010-G50Y
S 3050-Y30R	S 4020-Y10R	S 5005-G50Y	S 5502-B	S 7010-G70Y
S 3050-Y40R	S 4020-Y20R	S 5005-G80Y	S 5502-R	S 7010-G90Y
S 3050-Y50R	S 4020-Y30R	S 5005-R20B	S 5502-Y	S 7010-Y10R
S 3050-Y60R	S 4020-Y40R	S 5005-R80B	S 6000-N	S 7010-Y30R
S 3060-Y30R	S 4020-Y50R	S 5005-Y20R	S 6005-B20G	S 7010-Y50R
S 3060-Y50R	S 4020-Y60R	S 5005-Y50R	S 6005-G80Y	S 7010-Y70R
S 3060-Y60R	S 4020-Y70R	S 5005-Y80R	S 6005-R50B	S 7010-Y90R
S 3500-N	S 4020-Y80R	S 5010-B50G	S 6005-Y20R	S 7020-Y70R
S 3502-B	S 4020-Y90R	S 5010-G50Y	S 6005-Y50R	S 7500-N
S 3502-G	S 4030-G30Y	S 5010-G70Y	S 6005-Y80R	S 7502-R
S 3502-R	S 4030-G50Y	S 5010-G90Y	S 6010-G50Y	S 7502-Y
S 3502-Y	S 4030-Y	S 5010-Y10R	S 6010-G90Y	S 8000-N
S 4000-N	S 4030-Y10R	S 5010-Y30R	S 6010-R30B	S 8005-G50Y
S 4005-B20G	S 4030-Y20R	S 5010-Y50R	S 6010-Y10R	S 8005-G80Y
S 4005-B80G	S 4030-Y30R	S 5010-Y70R	S 6010-Y30R	S 8005-Y20R
S 4005-G20Y	S 4030-Y40R	S 5010-Y90R	S 6010-Y50R	S 8005-Y50R
S 4005-G50Y	S 4030-Y50R	S 5020-B90G	S 6010-Y70R	S 8005-Y80R
S 4005-G80Y	S 4030-Y60R	S 5020-G90Y	S 6010-Y90R	S 8010-Y10R

Finish - liquid

Whereas all indications and recommendations supplied herein are stated to the best of our experience and knowledge, they should be considered as indicative only and should be confirmed by exhaustive practical applications. Diasen doesn't know the peculiarity of the processing, or the characteristics of the support. Therefore the applicator should carry out preliminary tests, to verify the suitability to the foreseen application, and in any case he will take the responsibility of the intended use. In case of uncertainties or doubts, please contact the company's technical department, provided that this is only a simple assistance for the applicator: he should have the appropriate capabilities and experience to determine the more suitable solution. Always respect the latest update of the technical sheet available on www.diasen.com.

ACRILID PROTECT COATING

Coloured finishing for indoor and outdoor, resistant to salty air

CUSTOMIZED NCS COLOUR

S 8010-Y50R
S 8500-N

S 8502-Y

S 8505-G80Y

S 8505-Y20R

S 8505-Y80R



Finish- liquid

DIASEN Srl - Z.I. Berbentina, 5 - 60041 Sassoferrato (AN)
Tel. +39 0732 9718 - Fax +39 0732 971899
diasen@diasen.com - www.diasen.com