

Product's description

Odourless insulating smoke-proof wall paint

Antifumo is a paint for internal use. Easy to apply, strong fixative power, it is successfully used even as distemper. It is steam-proof and odourless.

Practical advice

Suitable for bathrooms, kitchens, bars, cinemas and with high nicotine, soot, wood-smoke degree. It can be easily applied over old perfectly adhesive hydro-paints.

Technical features

Aspect		Matt
Colour		White
Density Kg/Lt.		1,35 ± 0,05
Viscosity 25°C		Thixotropic
Solid content by volume %		50 ± 2%
Theoretical spreading rate Sq.m/lt – gr/m ²		10 Sq.m./L. – 135 G/Sq.m.
Typical thickness humid/dry micron		100 humid / 50 dry
Mixing ratio Base/Hardener		Single-component product
Pot Life		Not applicable
Thinner		Ecosolv 380 odourless
Painting method	Brush	15 - 20% thinning
	Roller	20 - 25% thinning
	Spray	Not suitable
	Airless spray	Not suitable
Drying times 25°C	Untouched :	about 20 minutes
	Dry to the touch :	1 hour
	Absolutely dry :	24 hrs.
Min./ Max. overcoating times		24 hrs. / no limitation
Flash point		30°C
Shelf life		12 months
Standard package		Kg 5 - Kg 7 – Kg 20

Notes

If applied in environments, infected by nicotine and light soot, it is possible a hydro-paint over-applying, after 24-48 hrs.; while, for environments infected by strong wood-smoke, it is necessary to wait at least 5-7 days.

Application instructions

Preparation of the surfaces

- Masonry surfaces: Remove by broomcorn brush all the non adherent soot and the chalking plaster.
Putty with Atriamural stopper in successive stages. Sand and remove the dust. Apply a first coat by roller or brush. After 24 hrs., apply the second coat.
- It is also possible to apply the product over properly prepared and primed iron, galvanized iron, light alloy surfaces.
- Painted or new wood: well cleaned and sanded.
- Wood conglomerates (masonite, faesite, MDF): well cleaned and dry.

It is recommended for

- Internal surfaces of kitchens, bathrooms, bars, public places, food industries.

It is not recommended for

- Constant immersion.

Recommended finishes

- Idrolux semilucido, Idrolux lucido, Idropitture acriliche.

Safety precautions

- The product is inflammable.
If applied in closed places, it is necessary to air properly the room, to avoid it could be saturated by thinner fumes contained in it.

Tender Item

- Application of Antifumo, odourless, smoke-proof, high insulating, synthetic plasticizing resins and covering pigments based wall paint, to be applied in two coats, with a consumption of 0,250 l/Sq.m. or 270 g/Sq.m.

(*) These information, even if reliable, are absolutely approximate. The company owns the right to change them without any notice. Moreover, it is not responsible for the use of the present information. The user must previously test the product's suitability, before using it. For any further explanations or requirements on the products, please contact the staff of our technical lab.