



CSX.0245

CONSILEX ANTISMOG REMOVER

Specific cleaner for the removal
of smog and graffiti from walls

Dosage

0.3 kg /m²

Packaging

- Plastic can 5 kg
- Plastic can 25 kg
- Pail 5 kg
- Pail 25 kg

Application

- Brush
- Paint roller

Family
Consilex

Product Lines

- Building
- Opus
- Sanageb

Components
Single-component

Type

Soot cleaning treatments based on tensioactive agents

Functional Categories

- Roads and municipal maintenance interventions
- Deep cleaning of supports

Appearance
Liquid

General description

CONSILEX ANTISMOG REMOVER is an innovative product, designed for cleaning blackened external walls, especially encrusted by soot from pollution and smog. It is perfect for cleaning outside walls, external walls and roofs made of natural stone, exposed brickwork, reconstituted stone, concrete, etc.

General features

It is composed of special thickened surfactants, CONSILEX ANTISMOG REMOVER offers considerable advantages in terms of ease of application, safety and effectiveness, in contrast to generally used corrosive products. In the form of homogeneous gel, it can very easily be applied by brushing, without leaking. It does not contain soda and potassium, and does not need neutralisation after rinsing.


Fields of application


Removal of blackish incrustations produced by smog and soot deposits from the external walls of buildings and monuments and on all civil and industrial buildings.

Available colours

- Beige

Basic features

 Density:
0.85 kg/dm³


 Pot-life:
20 min

 Solvent-free

 Use wearing protective glasses

 Nonflammable

 Shelf-life:
12 months

 Temperature of use:
+5/+30 °C

 Use wearing protective gloves

Technical specifications

Boiling point/range: 100 °C

Not to be diluted

The product creates film

Tools cleansing

- Water

Applicable on

- Plasters
- Concrete
- Bricks
- Tuff
- Mixed walls (bricks and stones)
- Stone walls
- Rock walls

IF YOU WANT TO SOLVE IT
 azichem

www.azichem.com

Updated: 24/02/2018

General sales conditions and legal notices on

www.azichem.com/disclaimer

Instructions for use

The product is for use in its pure state, without diluting. Shake the package prior to use and carry out preliminary tests on a small portion of the surface before use.

Apply the product by brushing on the support to be treated for about 300 g/m² (variable depending on the type and porosity of the substrate). Then leave to work for about 30-60 minutes. Avoid letting the product dry completely on the support. Once the time required to ensure that the active ingredients have performed their cleaning action has passed, remove the product from the support with a 150 bar pressure washer.

Substrate preparation

Application support must be dry.

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Protect from humidity. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

Technical and performance data outlined in this document are the result of laboratory testing conducted in a conditioned environment, as such they can result as considerably changed from operating and application conditions. The need follows to carry out preliminary tests in actual use conditions.

The user is required to check the product's most recent Material Safety Data Sheet, reporting physical-chemical and toxicological data, risk phrases and other useful information on how to safely transport, use and dispose of the product and its packaging. It is also reminded that the product and its packaging must not be dispersed in the environment for any reason.

For perfect application, CONSILEX ANTISMOG REMOVER should be used when the temperature of the supports is between 5°C and 30°C. Do not use in case of rain, or very high temperatures (above 35°C).

Do not dilute or mix with other products. Do not apply on wet media. Do not apply on painted media, without carrying out accurate preliminary tests; some paints may indeed be damaged by applying the product.

Under normal conditions of use, which provide adequate ventilation, it is not necessary to use protective respiratory devices; wear protective masks in closed environments or with poor ventilation. Wear rubber gloves and safety glasses when handling the product.



www.azichem.com

Updated: **24/02/2018**
General sales conditions and legal notices on www.azichem.com/disclaimer

CONSILEX ANTISMOG REMOVER is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **24/02/2018**
General sales conditions and legal
notices on
www.azichem.com/disclaimer