

CRISTALLIZZANTE

Crystallizing for natural honed limestone stones and grits.

Surface Destination:

Floors and surfaces in natural calcareous stone sensitive to acids such as marble, grit and travertine. Do not use on ceramic, granite and slate coatings.

Properties:

CRISTALLIZZANTE is ideal for the crystallization of all natural limestone surfaces and grains sensitive to the action of acids. The product makes the treated surfaces shine by eliminating their porosity and making them resistant to wear, thanks to an increase in their resistance to traffic and trampling, as well as protecting them from scratches and from the formation of dirt. The colors of natural stone floors recover their brilliance and their original tone and keep them for a long time, thanks to a simple, fast and effective maintenance.

Performance - consumption:

Apply the product only on perfectly clean, degreased and dry surfaces, making sure there are no residues of wax or lead treatments. In the event that deep scratches are present on the surface or that grouting operations are to be carried out, it will be necessary to work beforehand with sanding operations, before applying CRISTALLIZZANTE. Shake the product well before use and use it preferably in a sprayer. CRISTALLIZZANTE is ready for use: spray the product evenly on the surface to be treated (approximately 3-4 sprays per square meter of surface) and start working immediately using a single-brush machine equipped with a steel wool disk, with a circular motion at a speed of 400 rpm. Work the product for a few minutes, until the desired degree of gloss is achieved. For a possible greater degree of gloss, apply CRISTALLIZZANTE again, repeating all the operations described above and work until the product is completely absorbed by the surface and there are no stagnations. If visible marks remain, wash with a white abrasive disk and a neutral detergent, removing the residues with a wet vacuum cleaner. It is possible to dry polish with a single brush equipped with a white disc to increase the final shine. Always carry out preliminary tests on the surface to be treated in order to avoid possible unwanted effects.

Technical Data:

- Appearance: beige liquid
- pH: 2.5 ± 0.5
- Specific Weight: 1,08 Kg / l $\pm 0,1$
- Packaging: Plastic bottle of 1 lt.

Performance:

For indicative purposes, 40-50 sqm. for lt. of product.

Specifications: Finishing polishing treatment consisting of a water-based emulsion of waxes and special crystallising agents for the crystallization of floors and surfaces in natural limestone, sensitive to acids such as marble, grit and travertine (type CRISTALLIZZANTE of CIR). The product must give brilliance and tone to the treated surfaces, in addition to an increase in their resistance to wear due to traffic and trampling. Needs to be easily applied using a single-brush machine equipped with a steel wool disk. The product in question must be equipped with a 16-section safety sheet as required by the legislation in force.

Warnings:

- Product intended for professional use.
- Operating temperature: + 5 ° C / + 35 ° C
- Carefully protect the surfaces to which the product is not intended.
- Equip operators as required by current safety regulations.
- Ventilate closed rooms adequately while using the product.

All information contained in our documentation corresponds to our best current technical knowledge and can not be considered binding because the real application conditions, verifiable on a case-by-case basis, may also involve significant changes both of the practices described above and of the results obtained. However, it is advisable to carry out preliminary tests in order to establish whether the product is suitable for the intended use and declines all responsibility for damages that may result from improper or incorrect use of the product. Do not disperse the product and processing residues in the environment.