



DET 186 TFR (FS)

CLEANER FOR EXTERNAL WASHING BOX OF ROLLING STOCK

DET 186 TFR (FS) is a special formulation designed for external washing of passenger cars, trucks, subways, trams and in general of all rolling stock of recent construction.

Finds application when a very energetic action is necessary for the removal of oils, greases and various pollutants from painted surfaces and unpainted rolling stock, bringing them back in excellent appearance conditions.

DET 186 TFR (FS), is a very concentrated product formulated with anionic and non-ionic surfactants, inorganic salts, organic sequestering agents, adjuvants .. and does not contain solvents.

It can be used either manually or with automatic equipment.

INSTRUCTIONS FOR USE

DET 186 TFR (FS) is used diluted with water depending on the need, the type and amount of dirt to be removed, the method of application, etc.

The optimum concentration depends on the user experience and dirty conditions to remove.

- **USER MANUAL**

The product is effective diluted to 2-3% in water.

Apply by spraying (using spear, nebulizer, mops, hand with sponges) starting from the bottom upwards; leave for a few minutes, brushing in the case of particularly stubborn dirt; rinse with water under pressure.

- **AUTOMATIC INSTALLATIONS**

Adjust the automatic dispenser of the detergent in such a way as to obtain on the spray nozzles a solution of between 1 and 3% (1% in summer and 3% in the winter period)

The step of rinsing and the drying phase will follow.

NOTE: DO NOT operate vehicles or convoys left in the sun during the period late spring / autumn. In this period, wet the means before applying the cleaning solution.

PRECAUTIONS

Before use refer to the material safety data sheet.

Issue: VNT 12/08