

ECO 7 G

Environmentally-friendly product for the removal of graffiti.

Surface destination:

Natural stones of any nature and artifact absorbent buildings, even historical-artistic or monumental buildings. Glazed and plastic surfaces, even high-temperature painted metal surfaces.

Properties:



Environmentally-friendly product based on particular esters, emulsifiers and biodegradable surfactants instead of harmful chlorinated solvents. ECO G 7 is a specific and selective product to eliminate all types of graffiti and soiling of vandalism. The balanced formulation allows that the product does not alter the appearance or texture of the surfaces and acting selectively only on graffiti and stains. ECO 7 G is also suitable for working on surfaces previously treated with anti-graffiti protective as ECO PMC 2000.

Use:

ECO 7 G is ready to use. Apply with a brush or roller, making sure that the surface to treat is completely dry. Leave it work for at least 10 minutes of non-absorbent surfaces, increasing the contact time even up to 12 hours on those that have a higher porosity and diffused layers as well as important graffiti stratifications; assist the action of the product with brushes or abrasive pads. In case of particularly tough, laminated and penetrated paints, you must remove with paper towels or rags the paints and inks dissolved by the first application, without rinsing because water inhibits its function. Then, re-apply ECO 7 G until the graffiti is completely dissolved. If necessary, repeat the operation. Finally, rinse thoroughly with water under pressure in order to remove any residual product. Wait for the drying in order to assess the effectiveness of the washing. Then standardize the degree of cleaning by applying the specific "RP-Line" detergent suited to the nature of the support. Determinate by preliminary tests the correct application methodology and the resistance of the support, in order to avoid possible side effects.

Technical data:

- Appearance: orange gel
- Specific gravity: 1 Kg/l
- Packaging: 2/5/10 litres plastic tanks.

Performance:

Approximately, 4-7 square meters for liters of product.

Capitolato: Environmentally-friendly product based on particular esters, emulsifiers and biodegradable surfactants instead of harmful chlorinated solvents, specifically formulated to eliminate graffiti and paints from natural stones and artifact absorbing buildings (like CIR's ECO 7 G). It must allow the rapid removal of all types of soiling and graffiti (spray paints, inks, pens etc.) present on the surfaces to which it is intended, without altering the appearance and texture of the materials. It must be accompanied by 16-section MSDS, as required by applicable law.

Warnings:

- Product for professional use.
- Applying temperature range +5° C / +35° C
- Do not apply under conditions of high humidity, imminent rain or full sun.
- Do not smoke during the application.
- Carefully protect the surfaces to which the product is not intended.
- Equip operators as required by current safety standards.
- Ventilate closed places when using the product
- Do not litter in the environment..

All information contained in our records correspond to our best knowledge of current techniques and cannot be considered binding or challenging as the real application conditions, verifiable case, may also result in major changes of both practices described above and the results obtained. Perform preliminary tests to determine if the product is suitable for the intended or not. We decline any liability for any damage resulting from improper use or misuse of the product. Do not litter in the environment. This data sheet replaces all previous versions.