



Family
Intotech

Type
Finishing putty and skims

Product Lines
• **Building**
• **Opus**
• **Sanageb**

Functional Categories
• **Reconstruction, repair and maintenance of wooden structures**
• **Plastering and loose-fill of cracks and cavities on plasters and facades**

Components
Single-component

Appearance
Paste

INT.0045

FIBROSTUCK

Reinforced fibre adhesive filler,
for filling fissures and cracks

Customs Code

3214 9000

Dosage

1.75 kg /dm³

Packaging

- Pail 5 kg

Application

- Finishing trowel
- Spatula

General description

Adhesive filler, white in colour, for grouting and filling cracks and fissures and small imperfections on plasters and external walls, also in combination with SANAXIL FILLER.

General features

FIBROSTUCK is specifically formulated for filling, for the regularisation and the levelling of different types of surfaces: concrete, mineral and cement plasters, wood, etc.; it is ready-to-use and must be remixed, slowly, only upon its application

The three-dimensional reinforcement of nylon fibres provides different levels of finishing and weaving; it can be recoated directly, without resorting to fixatives or insulation materials; it allows the construction of perfect bases for the subsequent application of finishing products.

Fields of application


Reclamation of the degenerative condition (cracks and discontinuities) of external walls, prior to the finishing operations, painting, etc.


Available colours

• White

Basic features

 Density:
1.75 kg/dm³

 Shelf-life:
12 months

 Temperature of use:
+8 / +35 °C

Technical specifications

Complete hardening (a 20°C): 24 - 48 h

Dry residue: 82.3 %

Hard to touch (a 20°C): 4 h

Tools cleansing

• Water

Applicable on

• Plasters
• Concrete
• Cement-based or lime-based mortars
• Drywall
• Wood
• Fiber-cement

Substrate preparation

The surfaces should be clean and free of any dirt, crumbling and non-adhering parts, dust, etc., conveniently saturated with water until they reach the condition "saturated with dry surface".

The cracks to be grouted should be preliminarily opened, cleaned, brushed and dedusted; where necessary they should also be treated with the fixative PROTECH FIX AC.

IF YOU WANT TO SOLVE IT
 **azichem**

www.azichem.com

Updated: **24/02/2018**

General sales conditions and legal notices on

www.azichem.com/disclaimer

Instructions for use

Work by spreading the product with a spatula or steel trowel, grouting or skimming with one or many coats, until achieving the correct filling and/or levelling.

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

Technical and performance data outlined in this document are the result of laboratory testing conducted in a conditioned environment, as such they can result as considerably changed from operating and application conditions. The need follows to carry out preliminary tests in actual use conditions.

The user is required to check the product's most recent Material Safety Data Sheet, reporting physical-chemical and toxicological data, risk phrases and other useful information on how to safely transport, use and dispose of the product and its packaging. It is also reminded that the product and its packaging must not be dispersed in the environment for any reason.

Avoid applying in conditions of rain and high humidity, which could compromise proper drying with consequent possibility of runoff that may continue for several days.

FIBROSTUCK is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **24/02/2018**
General sales conditions and legal
notices on
www.azichem.com/disclaimer