



Technical data sheet 11-18	N. D 1027	
GLASSTEX® GLASS MAT - Art. GM225P - Art. GM300P		
FIBREGLASS NEEDLED FABRIC IN E GLASS FIBERGLASS		
Product consisting of cutted glass filaments, randomly distributed, non-woven bonded by powder or liquid finish, for reinforcement of liquid membranes.		

FEATURES

BONDING AGENT	POWDER/LIQUID
LOSS BY CALCINATION GM225P	3-8 %
LOSS BY CALCINATION GM300P	2-8 %
FINISH CONTENT	< 0.2 %

CODE ART.	WEIGHT	ROLL HEIGHT	Kg per ROLL	N° ROLLS per BOX	N° BOX per PALLET
GM225P	225 g/m ²	125 cm	10	4	12
GM300P	300 g/m ²	125 cm	40	1	10

The indications reported in this documentation regarding the use or use of our products, while corresponding to our best experience and to the current state of our knowledge, are to be considered, in any case, purely indicative and do not involve any responsibility on the final result of the work. Therefore it is the responsibility of the buyer to verify the suitability of our products for the use and the purposes it is intended for. Biemme srl is not responsible for improper use of the material. Always refer to the latest updated version of the technical data sheet, available on the site: www.biemmebiagiotti.com. Biemme srl reserves the right to make changes at any time that it deems appropriate without any notification.

