

HydroFlex Primer is a deep cleaning preparation specifically to be used before applying HydroFlex surface treatments. Its unique formulation ensures removal of all grease and soils and also enables a tight bond between the substrate and the treatment to ensure long lasting performance.

With built in rust inhibitor, **HydroFlex Primer** should be used before treating any surface.

Suitable for all types of gel coat, plastic, painted and metal substrates, **HydroFlex Primer** is a non streak, pre-wash treatment that prepares the surface to allow the appropriate bonding to take place. In order to guarantee the surface treatment will perform as stated it is absolutely necessary to use HydroFlex Primer to prepare the surface prior to treatment.

Coverage: 240m² per diluted litre

Application

As part of the Coating process, dilute **HydroFlex Primer** 1 part product to 10 parts water and use sparingly with a microfiber cloth or mop. Ensure all the surface has been washed in the **HydroFlex Primer** then rinse off with clean water.

Make sure the surface is completely dry before applying and HydroFlex Surface treatments.

ECO.3[®] System

The HydroFlex range is suitable for use in any industrial or domestic application and is designed to be used as part of the Hydros ECO.3 System. The ECO.3 System has three unique stages: **Clean; Coat; Care**. Initial cleaning is done to provide a soil free surface, then the HydroFlex treatments are applied to the substrate to increase surface performance. Finally, the resulting surface is cleaned using **HydroSafe** non-caustic cleaning solutions. Cleaning times can be reduced by as much as 50% allowing machinery to be back in production faster.

Product Order Codes

HFX-PRC500M 500ml

HFX-PRC1L 1 litre

General Product Properties

Easy to clean

Prevents Corrosion

High coverage per litre

Prepares surface for treatment

Component of ECO.3 System



ECO.3[®] Compatible Product

Hydros Solutions Limited
Beckbridge House, Beckbridge Road, Normanton Industrial Estate
Normanton, WF6 1TE, United Kingdom.

Phone: +44 (0)1924 688 045
E-mail: info@hydrossolutions.com

Fax: +44 (0)1924 894 066
Web: www.hydrossolutions.com