



RIMOX GRAF A

ANTIGRAFFITI WATER BASED PAINT

RIMOX GRAF A is a **viscous** single-phase paint stripper, low odor, designed for the removal of resistant finishes such as: epoxy, epoxy primers, polyurethane, alkyd and other catalysed paints.

THANKS TO ITS VISCOSITY JOINS EASY TO VERTICAL SURFACES, WET STAYING FOR A LONG PERIOD, **SIGNIFICANTLY REDUCES THE CONSUMPTION OF THE PRODUCT AND THE EXTENSION OF CONTACT TIME WITH BETTER RESULTS.**

RIMOX GRAF A offers significant benefits for the safety of the workplace as "**free**" of chlorinated solvents, petroleum solvents, phenols, chromium, ammonia, amines, organic or inorganic acids.

It can also be applied to aluminum alloys, steel, cast iron when used as indicated.

INSTRUCTIONS FOR USE

Application:

It is recommended that the ambient temperature is not lower than 15 -18 ° C.

Lower temperatures can slow or stop the paint stripper action.

Apply RIMOX GRAF A on the surface to be painted in a uniform layer, at least 1-2 mm.

Apply the product by means of roller or brush.

Leave it to act for a time between 10 and 45 minutes depending on the layers to be removed

The speed of action increases with the temperature increase.

DO NOT apply the product to plastic or rubber materials.

Removal:

Remove the bulk of the paint stripper does not react and the detached paint with a squeegee.

Rinse with water and then pressurized with a pressure washer.

If necessary, repeat the application of the paint stripper in areas that require it, making sure to wait for the drying of the surface before the new application.

STOCCAGGIO

Il prodotto in confezioni originali va stoccato ad una temperatura compresa tra 5 °C e 35 °C, lontano da sostanze incompatibili ed in luogo ventilato.

PRECAUTIONS

Before use refer to the material safety data sheet.

Issue: AB 03/09