

# STABILWET

## CHARACTERISTICS

Revitalizing and water-repellent treatment based on polysiloxane resins in a water-based dispersion, specific for the surface application on paving in natural bound and stabilized aggregate.

### TECHNICAL SPECIFICATIONS

Appearance	Liquid
Colour	White
Storage life	12 months
Presence of solvents	NO

### ADDITIONAL INFORMATION

Flammability	No
Personal protective equipment to be used	Gloves

### STORAGE

Store the product in its original container in a cool, dry place, protected from direct sunlight, at a temperature between +10 °C and +30 °C. Protect from frost. Inadequate storage of the product may cause the loss of its characteristics.

#### PACKAGE

25 kg tank

#### CONSUMPTION

Minimum application of 200 g/m<sup>2</sup> for each coat

#### APPLICATION

Low-pressure airless nebulization, long bristle brush, roller

### FIELDS OF APPLICATION

Revitalizing and water-repellent surface treatment to highlight and maintain over time the chromatic and aesthetic characteristics of the aggregate present in the paving, for application on cycle paths, footpaths, rural roads, forest roads, paths in parks and gardens, cemetery roads, sports facilities, playgrounds, car parks, golf courses, squares, archaeological sites and any other support made of natural soil or bound and stabilized aggregate.

### METHODS OF APPLICATION

STABILWET must be applied by means of low pressure airless nebulization or brush/roller on the surface of the paving, which is dry and free from debris.

The minimum dosage to be applied is 200 g/m<sup>2</sup> for each coat. For the initial treatment we recommend the minimum application of 2 coats, applying the second after drying. The product can be used periodically as a maintenance treatment, where necessary. Our technical staff is available to provide useful information for the best use of the product.

## WARNING

Please note that the user is required to take view of the latest Product Safety Data Sheet, containing chemical-physical and toxicological data, risk phases and other information in order to transport, use and dispose of the product and its packaging in complete safety. It must be recalled, however, that you must not dispose of the product and its packaging in the environment. The information contained in this technical data sheet, while referring to our best experience, is to be considered in any case indicative and therefore the user is recommended to carry out any test necessary to verify the suitability of product. The user is required to determine whether the product is suitable for the intended use and in any case assumes any responsibility arising from its use.

## IMPORTANT RECOMMENDATIONS

Depending on the high variability of the chromatic and finishing characteristics that can be obtained in the paving in natural bound and stabilized aggregate, linked to the variety of the nature of the aggregates that may be used, it will be necessary to evaluate from time to time the number of coats of STABILWET to apply, depending on the yield and the desired aesthetic effect. For the programming of a periodic maintenance treatment, deigned to maintain the revitalizing effect over time, the progressive evolution of the surface appearance of the paving must be verified, intervening as necessary.

## MANUFACTURER/DISTRIBUTOR

STABILWET is manufactured/distributed by TERRA SOLIDA, an exclusive brand of Promotec Srls.

Update of 16/05/2018