

FluxerA

COLD MIX ASPHALT ADDITIVE & BITUMEN DIS-SOLVER

DESCRIPTION



FluxerA, It is an additive to use in cold mix asphalt production for asphalt road and pavement maintenance.

ADVANTAGES

Cold mix repair asphalt can be use in "cold" and "humid" weather condition if added FluxerA
It is not de-graded or alter the performance of asphalt
It is not required any special equipment and tools. Application is simple and comfortable.
The road and repaired area can open traffic immediately without any problem.

APPLICATION

There is no contain TAR, NEFT, Base oil or white spirit. It gives high workability and plastifity to the mixture. Cold mix asphalt can be store in weather sealed plastic bag or stack upto 6 months.
FLUXERA adding the mixture after bitumen addition. Bitumen penetration 70/100 and dosage 4-4,5%

DOZAJ

FLUXERA uses 20-25% of bitumen weight. Agregate 3 – 6 mm range . Production temperature maximum 110 degrees celsius

FİZİKSEL ÖZELLİKLERİ

Apperance	Liquid
Density (20°C)	0,85 ± 0,02 g/cm ³
Viscosity (25°C)	6 ± 1 cP
Flamming Point	> 100 °C

Made by hydrocarbons & oxo-alchols

DEPOLAMA VE AMBALAJ

Keep protected rain, snow conditions. Keep away from heat sources and open flame.

Packing in 180 kg barrels or 900 kg IBC tanks