

LINE	Retailers
Code	UMBRELLA FINITURA
Revision	1
Year	2016

Product type **UMBRELLA Finitura**

Glossy transparent water-based finish, for indoors and outdoors; non-toxic and non- flammable.

Umbrella finitura is a synthetic and modified resin-based paint in aqueous dispersion in nanotechnology, with internal molecular lamination that is highly transparent and non- yellowing. The Umbrella finitura lucida o satinato is characterised by an optimal and prolonged resistance to ultraviolet rays, high unsaponificability, excellent water vapour permeability, good drying, optimal tough elastic coefficient, optimal water resistance.

Use For balconies and terraces with exposed tiles requiring a waterproofing effect.

Technical characteristics

Aspect of the dry film colour	Shiny/satin (non-slip)
Colour in the container	Milky
Density	Kg/Lt 1,10 ± 0,05
Viscosity of the product 25°C	150 - 200 " Ford 4
Volumetric dry residue %	47 ± 2%
Theoretical coverage	100 gr/mq
Typical micron thickness	25 dry 75 humid
Mixing ratio Base/Hardener	Mono-component product
Pot Life	Non aplicable
Dilution	As is - Do not dilute
Application method	Brush, Roller - application in one or more coats
Drying 25°C	Without touching: 1 hour Dry to the touch: 3 hours Completely dry: 12 hours
Resistance for operating temperature	100°C
Minimum / Maximum second coating	12 hours / unlimited
Flammability point	Non-flammable
Cold resistance	Until -30°C tested
Storage stability	24 months in original unopened packaging and stored in a dry place with minimum temperatures of 7°C and maximum of 35°C.
Standard Packs	0,750 lt - 5 lt - KIT UMBRELLA

Colorificio Atria S.r.l.

C/da Camarro - Formeca
91028 Partanna (TP)
Tel. 0924/49500 - 0924/87610
Fax: 0924/921250
P. IVA 00013450812

E-mail: info@atria.it
web site www.atria.it

Application standards **Preparation of tiled surfaces.**

Clean, with appropriate means, any dirt, stains and grease. Check that the spaces are filled tightly, in a compact manner and without missing spots, possibly repairing them with special mortar. Apply Umbrella primer and wait until it dries completely. After at least 12 hours apply Umbrella finitura in one or more coats, as necessary with a 12-hour interval between each coat.

Application notes: Apply in favourable weather conditions, with a minimum temperature of +8°C and a maximum of +35°C, with maximum air humidity of 75%. Do not apply on surfaces exposed to direct sunlight or possible rain or strong wind. The treated external surfaces must be protected for at least 48 hours after application. Clean the tools with water immediately after use.

Recommended for Tiled surfaces, concrete, plaster, natural and artificial stones. Urban, rural and marine atmosphere

Not recommended for Immersion in water and heavy industrial atmospheres.

Suggested base-coats Umbrella Primer

Safety information The product is not flammable. Comply with the hygiene standards provided in the existing regulations for application. Do not dispose of the product or the container in the environment. For more information refer to the relevant safety data sheet.

(*) This information, even if reliable, you must consider them right, but the Company can change them any time without notice. The company has not responsibility for the uncorrected use of information. The responsibility is of who use the product, please check before the using. For more information of the product you can contact a technical responsible of laboratory.

Colorificio Atria S.r.l.

C/da Camarro - Formeca
91028 Partanna (TP)
Tel. 0924/49500 - 0924/87610
Fax: 0924/92250
P. IVA 00013450812

E-mail: info@atria.it
web site www.atria.it