

LINE	Retailers
Code	UMBRELLA PRIMER
Revision	1
Year	2016

Product type **UMBRELLA Primer**

**Mono-component water-based transparent primer, anchoring adhesion promoter.**

Umbrella primer is a mineral organic natural compound, designed specifically to promote adhesion on difficult surfaces. It is a product that is applied easily and free from harmful substances and organic solvents. Umbrella primer is not flammable and it is not harmful or pollutant.

Campi di impiego For balconies and terraces with exposed tiles requiring a waterproofing.

Technical characteristics

Aspect of the dry film colour	Transparent Opaque
Colour in the container	Milky
Density	Kg/Lt 1,10 ± 0,05
Viscosity of the product 25°C	16 sec. Ford 4
Volumetric dry residue %	25 ± 1%
Theoretical coverage	50 gr/mq
Typical micron thickness	30 humid 10 dry
Mixing ratio Base/Hardener	Mono-component product
Dilution	As is - Do not dilute
Application method	Brush, Roller - application in one or more coats
Drying 25°C	Without touching: 1 hour Dry to the touch: 6 hours Completely dry: 18 hours
Minimum / Maximum second coating	24 hours / unlimited
Flammability point	Non-flammable
Cold resistance	Until -30°C tested
Storage stability	12 months in original unopened packaging and stored in a dry place with minimum temperatures of 7°C and maximum of 35°C.
Standard Packs	0,375 lt - 2,5 lt - KIT UMBRELLA

Note: This is a caustic product, avoid contact with the skin and eyes. Protect wood, aluminum and Note glass surfaces. Protect surfaces from rain by treating with Umbrella primer at least 12 hours after application. Do not apply in presence of wind or possible rain

**Colorificio Atria S.r.l.**

C/da Camarro - Formeca  
91028 Partanna (TP)  
Tel. 0924/49500 - 0924/87610  
Fax: 0924/921250  
P. IVA 00013450812

E-mail: [info@atria.it](mailto:info@atria.it)  
web site [www.atria.it](http://www.atria.it)

Application standards **Preparation of surfaces.**

Clean, with appropriate means, any dirt, stains and grease. Repair any damage and peeling of existing spaces and apply one coat of Umbrella primer with a roller or brush. After at least 12 hours apply Umbrella finitura in one or more coats, as necessary with a 12-hour interval between each coat.

Recommended for Tiled surfaces, stoneware, ceramic, brick, concrete, plaster, natural and man-made exposed tiles.

Not recommended for Immersion in water and heavy industrial atmospheres.

Recommended Umbrella Finitura  
intermediaries and finishings

Safety information The product is not flammable. Comply with the hygiene standards provided in the existing regulations for application. Do not dispose of the product or the container in the environment. For more information refer to the relevant safety data sheet.

(\*This information, even if reliable, you must consider them right, but the Company can change them any time without notice. The company has not responsibility for the uncorrected use of information. The responsibility is of who use the product, please check before the using. For more information of the product you can contact a technical responsible of laboratory.

**Colorificio Atria S.r.l.**

C/da Camarro - Formeca  
91028 Partanna (TP)  
Tel. 0924/49500 - 0924/87610  
Fax: 0924/921250  
P. IVA 00013450812

E-mail: [info@atria.it](mailto:info@atria.it)  
web site [www.atria.it](http://www.atria.it)