

# **AntiBacterical Spray**

Scheda Tecnica Revisione :

del :

building paint

## **Type of product**

#### Sanitizing spray for walls whitening and anti-mold effect.

**AntiBacterical Spray** is a spray solution, specifically formulated to prevent and combat the formation of bacteria, particularly suitable for the preparation and restoration of wall surfaces that need cleaning and thorough sanitation, effectively heals internal wall surfaces contaminated with mold, algae and lichens.

### **Fields of application**

For surfaces of any nature, new or already painted, interiors of homes, kitchens, hospitals, schools, barracks, dairies, pasta factories, breweries and public and private premises where a strong anti-mold, fast-acting algae action is required and sanitizing.

## **Technical characteristics**

Appearence<br/>Density<br/>Theoretical yieldStraw liquid<br/>1,05 ± 0,05<br/>15 – 20 Sq.m./LtDilution<br/>Minimum reaction timeApply as it is<br/>10 - 15 minutes (according to surface degradation)Storage stability<br/>Standard packs12 months<br/>Lt. 0,750

Store the product at room temperature away from sunlight and in its tightly closed containers. Not apply the product with temperatures lower than + 5  $^{\circ}$  C and higher than + 40  $^{\circ}$  C with relative humidity higher than 85%



# **AntiBacterical Spray**

Scheda Tecnica Revisione :

del :

building paint

### **Rules of application**

#### **Preparation of wall surfaces**

Apply AntiBacterical Spray with a special spray applicator on the areas to be treated, at a distance of 10 - 20 cm, let react for 10 - 15 minutes according to surface degradation, then brush and clean the surface, with damp cloth or sponge.

If necessary in case of extreme surface degradation or presence of (residual) mold, repeat the operations previously indicated.

It is possible to paint the treated surface after 30 minutes from the application on a dry surface. After use, unscrew and rinse the trigger, then screw the cap back on

It is recommended for: In public and private environments with high intensity and bacterial containment.

It is not recommended for: Constant immersion with water.

	Colorificio Atria S.R.L.
Country Phone Online Email	Contrada Camarro Formeca 91028 Partanna (Tp) Italy +39 0924 49500 / 0924 87610 / Fax 0924 921250 www.atria.it info@atria.it
Business Assurance	Quality ISO 9001:2015 / Enviromental ISO 14001:2015 DNV·GL

Social Media

@ColorificioAtria @atria.madeinpaint



Colorificio Atria



(\*) This information, although believed to be reliable, must be considered indicative, the company reserves the right to change them without notice. The use of this information does not imply any responsibility on our part, including the violation of any license. It is the responsibility of the users to check in advance the suitability of the product for the specific use. For further clarifications or specific requests regarding the products, please contact the head of the technical laboratory.