



BUCKET 15 L

CALCEPURA
La tradizione della calce.

FONDO TRASPIRANTE

natural hydraulic lime material NHL 3.5

CALCEPURA FONDO TRASPIRANTE is a filling, highly masking bonding primer. Its special grain size ensures excellent anchorage of the finish to the substrate and uniformity in its absorption. Ideal as an intermediate on plasters affected by microshrinkage cracks.

TYPE OF SUPPORT

Traditional or premixed civil plasters based on hydraulic lime.

COMPOSITION

Dispersion of selected mineral fillers with a maximum thickness of 600 µ, in resin dispersion.

LABELLING

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: Does not require labeling.

TECHNICAL DATA

Appearance	Matt sandblasted effect
Volumetric mass	1.660 kg/l +/- 0.03
Dry residue	72% +/- 2
Ph	8 - 8,5
Environmental conditions of application	+5 / +30 °C - R.H. Max. 65%
Drying time	Dry to touch wait: 2/3 h - next layer wait: 5/6 h
Water dose	10 - 15% depending on substrate absorption
Yield	With one coat: 5/6 m ² /l (depending on the degree of absorption of the substrate)
Grain size	Max 0.6 mm
Application	Brush
Color	White

SUBSTRATE PREPARATION

Substrates must be dry, thoroughly cleaned, uniform in absorption. In case of chalking (plasters) or flaking (old paints), restoration of substrate integrity is recommended.

STORAGE

Min temperature: 5° C - Max temperature: 30° C. In the original packaging and properly stored indoors in a dry place, the product retains its characteristics for about 12 months.

The data and information contained in this sheet are the result of the knowledge available at the date of publication. Esincalce srl assumes no responsibility for damage to persons or property that may result from use of the product other than that for which it was intended. The sheet does not replace but supplements the texts or regulations governing the activity of use. The user is fully responsible for the precautions necessary for the use of the preparation. For anything not listed, refer to the product safety data sheet on our website esincalce.com or write to info@esincalce.com